

# NOVO-GLOSS TRIO™

NOW MEASURING GLOSS IS AS EASY AS...

**1** SIMPLE

**2** RELIABLE

**3** ACCURATE



**RHOPOINT**  
INSTRUMENTS

TAKE A CLOSER LOOK AT SURFACE QUALITY

## FEATURES

### TRUE TRIPLE ANGLE OPERATION

- 20°** High gloss surfaces such as automotive paint finish, polished metals and plastics
- 60°** Universal gloss measurement angle for all applications
- 85°** Matt surfaces such as automotive interiors, architectural paints and wood finishes
- 20°/60°/85°** Measure or calibrate all three angles simultaneously

### CONTINUOUS READ

Assess gloss variations on a large surface in seconds

### FLEXIBLE CALIBRATION

Calibrate on a standard that matches your sample for improved gloss control. Additional standards available from matt to mirror finish

### STATISTICAL ANALYSIS

Automatic calculation of batch statistics

### USB DOWNLOAD OF DATA

Download your results to Novo-Soft for further analysis, reporting and storage

## EXTRAS

### FREE EXTENDED WARRANTY

Register for a two year comprehensive guarantee

### FREE LIGHT SOURCE WARRANTY

Guaranteed for the life of the instrument

### UKAS CALIBRATION

Instruments and calibration tiles are available with ISO 17025 certification

### CALIBRATION AND SERVICE

Fast and economic service via our global network of accredited calibration and service centres

A2B-Lab  
Rue Ibnou Katir - Résidence El Beida, Imm. B, Apt. 22  
20380 Casablanca - Maroc  
Tél: +212 (0)5 22 98 66 19 Email: [contact@a2b-lab.ma](mailto:contact@a2b-lab.ma)  
[www.a2b-lab.ma](http://www.a2b-lab.ma)

N°Direct 0802 00 00 33

## ACCESSORIES

- Integrated BAM traceable calibration standard
- Calibration tile cleaning kit
- Quick-start guide
- USB cable
- Protective instrument case
- 4 x AA high power batteries
- Novo-Soft™ QA software CD
- Full instruction manual in PDF format
- Screwdriver



## SPECIFICATIONS

Resolution	0.1GU
Repeatability	0.1%
Reproduceability	0.5%
Battery life	15,000+ readings
Languages	EN, FR, D, NL, ESP, IT, TR, CZ
Measurement Area	20°: 10.5mm circle 60°: 10 x 20mm elipse 85°: 10 x 54mm elipse
Measuring Range:	20°: 0 - 2000 GU 60°: 0 - 1000 GU 85°: 0 - 150 GU

## CONFORMITY

International standards:

BS EN ISO 2813  
ASTM D523  
ASTM D2457  
DIN 67530  
JIS 8741  
ISO 7668



Certificate no: FM 29741



Beeching Road, Bexhill-on-Sea, East Sussex TN39 3LG. UK  
T +44 (0) 1424 739622 F +44 (0) 1424 730600  
[sales@rhopointinstruments.com](mailto:sales@rhopointinstruments.com) [www.rhopointinstruments.com](http://www.rhopointinstruments.com)